

WHAT IS CLAIMED IS:

1. A processor control apparatus for controlling a plurality of arithmetic units, said processor control apparatus comprising a plurality of instruction control units for issuing a series of instructions to said plurality of arithmetic units, some of said instruction control units being operable to switch between a first execution process for driving said plurality of arithmetic units by means of a single series of instructions and a second execution process for driving said plurality of arithmetic units by means of a plurality of different series of instructions, respectively.

2. The processor control apparatus according to claim 1,
wherein said some instruction control units each perform a switching process for switching between said first execution process and said second execution process according to information which is contained in advance in a series of instructions.

3. The processor control apparatus according to claim 1,
wherein when an M-th one of said instruction control units issues a second series of instructions to an N-th one of said arithmetic units which is performing said second execution process based on a first series of instructions issued by an N-th one of said instruction control units different from said M-th instruction control unit, said M-th instruction control unit is set in a wait state until said N-th arithmetic unit completes said second execution process.

4. The processor control apparatus according to claim 1, further comprising a first storage element for holding a plurality of series of instructions,

wherein when an M-th one of said instruction control units issues a second series of instructions to an N-th one of said arithmetic units which is

performing said second execution process based on a first series of instructions issued by an N-th one of said instruction control units different from said M-th instruction control unit, said second series of instructions from said M-th instruction control unit are stored in said first storage element, and

wherein said N-th arithmetic unit executes instructions which are stored in said first storage element based on information contained in said first series of instructions issued by said N-th instruction control unit.

5. The processor control apparatus according to claim 1, further comprising a second storage element which operates to hold, when one of said arithmetic units executing a series of instructions from one of said instruction control units is switched to execute a series of instructions from another instruction control unit, data generated by the series of instructions under execution by associating the data with that instruction control unit which is executing the series of instructions.

6. The processor control apparatus according to claim 1,
wherein it is determined, based on an instruction executing state of each arithmetic unit, one of said arithmetic units to which a new series of instructions is to be issued by one of said instruction control units, and

wherein said one instruction control unit is controlled based on the result of the determination so that the new series of instructions are directed to said one arithmetic unit thus determined.

7. The processor control apparatus according to claim 1,
wherein each of said series of instructions includes a VLIW type instruction.

8. The processor control apparatus according to claim 1,
wherein each of said series of instructions includes a series of time sharing instructions for serially driving a plurality of ones of said arithmetic

a wait state, and an instruction decoder of said second predetermined arithmetic unit does not output a switching instruction to its associated selector if a process is being executed by said second predetermined arithmetic unit upon issuance of said synchronizing instruction, and does not release the wait state of said first predetermined arithmetic unit until said second predetermined arithmetic unit completes said process.

13. The processor control apparatus according to claim 10, further comprising:

an instruction queue for temporarily storing, at a stage prior to said selector, a series of instructions to be transmitted from a second one of said instruction memories different from a first one of said instruction memories which stores a series of instructions being executed by said first predetermined arithmetic unit; and

a determiner for determining, based on a series of instructions being executed, whether or not the process being performed by said first predetermined arithmetic unit can be interrupted, said determiner operating to output, if the process can be interrupted, an interrupt signal for interrupting the issuance of the series of instructions to said first instruction memory which is a source of the series of instructions being executed, and generate a switching instruction to said selector to switch to a series of instructions from said instruction queue.

14. The processor control apparatus according to claim 10,

wherein each of said series of instructions includes a VLIW type instruction.

15. The processor control apparatus according to claim 10,

wherein each of said series of instructions includes a series of time sharing instructions for serially driving a plurality of ones of said arithmetic units.

16. The processor control apparatus according to claim 10, further comprising power control elements for controlling power supply to said arithmetic units based on their instruction executing states.

17. A processor control apparatus comprising:

a single instruction memory for storing a plurality of series of instructions to be executed by a plurality of arithmetic units;

an instruction decoder for decoding a series of instructions from said instruction memory, and outputting a decoded result to any of said plurality of arithmetic units; and

a selector for selectively switching between a plurality of series of instructions from said instruction memory to be decoded by said instruction decoder, and supplying a series of instructions thus selected to said instruction decoder;

wherein said instruction memory has a plurality of ports for issuing said series of instructions to said respective instruction decoders.

18. A processor control apparatus for controlling a plurality of arithmetic units, said processor control apparatus comprising a plurality of instruction control units for instructing said arithmetic units to execute a series of instructions,

wherein each of said instruction control units includes:

an instruction memory for storing a plurality of series of instructions;

and

an instruction decoder for decoding a series of instructions and supplying the decoded series of instructions to an associated one of said arithmetic units, and

wherein some of said instruction control units each have an instruction control selector for selectively switching between a first series of instructions from a first instruction memory of one of said instruction control

units and a second series of instructions from a second instruction memory of another instruction control unit different from said one instruction control unit to output one of said first and second series of instructions thus selected to said instruction decoder,

wherein each of said arithmetic units includes:

a first register file and a second register file for storing data generated by said first and second series of instructions, respectively, which are supplied from said first and second instruction memories and decoded by an instruction decoder of an associated one of said instruction control units; and

an arithmetic unit selector for selectively switching between said data generated by said first and second series of instructions being executed and stored in said first and second register files, respectively, according to an instruction from said associated instruction decoder to supply a selected one of said first and second series of instructions to a calculator.

19. The processor control apparatus according to claim 18,
wherein each of said series of instructions includes a VLIW type instruction.

20. The processor control apparatus according to claim 18,
wherein each of said series of instructions includes a series of time sharing instructions for serially driving a plurality of ones of said arithmetic units.

21. The processor control apparatus according to claim 18, further comprising power control elements for controlling power supply to said arithmetic units based on their instruction executing states.

22. A processor control apparatus for controlling a plurality of arithmetic units, said processor control apparatus comprising a plurality of instruction control units for instructing said arithmetic units to execute a series of

instructions,

wherein said instruction control units have a single instruction memory used in common for storing a plurality of series of instructions, and each includes an instruction decoder for decoding a series of instructions and supplying the decoded series of instructions to an associated one of said arithmetic units, and said single instruction memory has a plurality of ports for issuing said series of instructions to said respective instruction decoders,

wherein some of said instruction control units each having an instruction control selector for selectively switching between a first series of instructions and a second series of instructions both from said single instruction memory to output one of said first and second series of instructions thus selected to said instruction decoder,

wherein each of said arithmetic units includes:

a first register file and a second register file for storing data generated by said first and second series of instructions, respectively, which are supplied from said single instruction memory and decoded by an instruction decoder of an associated one of said instruction control units; and

an arithmetic unit selector for selectively switching between said data generated by said first and second series of instructions being executed and stored in said first and second register files, respectively, according to an instruction from said associated instruction decoder to supply a selected one of said first and second series of instructions to a calculator.

23. A processor comprising:

a plurality of arithmetic units; and

a plurality of instruction control units for issuing a series of instructions to drive said arithmetic units in a controlled manner;

wherein some of said instruction control units are operable to switch between a first execution process for driving said plurality of arithmetic units by means of a single series of instructions and a second execution process for driving said plurality of arithmetic units by means of a plurality of different

in a controlled manner,

wherein each of said instruction control units includes:

an instruction memory for storing a plurality of series of instructions;

and

an instruction decoder for decoding a series of instructions and supplying the decoded series of instructions to an associated one of said arithmetic units, and

wherein some of said instruction control units each have an instruction control selector for selectively switching between a first series of instructions from a first instruction memory of one of said instruction control units and a second series of instructions from a second instruction memory of another instruction control unit different from said one instruction control unit to output one of said first and second series of instructions thus selected to said instruction decoder,

wherein each of said arithmetic units includes:

a first register file and a second register file for storing data generated by said first and second series of instructions, respectively, which are supplied from said first and second instruction memories and decoded by an instruction decoder of an associated one of said instruction control units; and

an arithmetic unit selector for selectively switching between said data generated by said first and second series of instructions being executed and stored in said first and second register files, respectively, according to an instruction from said associated instruction decoder to supply a selected one of said first and second series of instructions to a calculator.

27. A processor comprising:

a plurality of arithmetic units;

a plurality of instruction control units for driving said arithmetic units in a controlled manner,

wherein said instruction control units have a single instruction memory used in common for storing a plurality of series of instructions, and

each includes an instruction decoder for decoding a series of instructions and supplying the decoded series of instructions to an associated one of said arithmetic units, and said single instruction memory has a plurality of ports for issuing said series of instructions to said respective instruction decoders,

wherein some of said instruction control units each having an instruction control selector for selectively switching between a first series of instructions and a second series of instructions both from said single instruction memory to output one of said first and second series of instructions thus selected to said instruction decoder,

wherein each of said arithmetic units includes:

a first register file and a second register file for storing data generated by said first and second series of instructions, respectively, which are supplied from said single instruction memory and decoded by an instruction decoder of an associated one of said instruction control units; and

an arithmetic unit selector for selectively switching between said data generated by said first and second series of instructions being executed and stored in said first and second register files, respectively, according to an instruction from said associated instruction decoder to supply a selected one of said first and second series of instructions to a calculator.

28. A processor controlling method usable with a plurality of instruction control units for controlling a plurality of arithmetic units to execute a plurality of series of instructions, said method comprising the steps of:

prescribing, in advance in a series of instructions which is to be performed, synchronous execution in which a plurality of predetermined ones of said arithmetic units are synchronously driven by a single series of instructions, or independent execution in which the plurality of predetermined arithmetic units are independently driven by a plurality of respective series of instructions; and

switching between the predetermined arithmetic units for performing a series of instructions based on the contents of the prescription therein.